



5400 Firmware Update Instructions

Scope

Firmware D4MU004 is applicable to all configurations 1.9TB and under:

MTFDDAV240TGC

MTFDDAV240TGA, MTFDDAV480TGA, MTFDDAV960TGA

MTFDDAK240TGA, MTFDDAK480TGA, MTFDDAK960TGA, MTFDDAK1T9TGA

MTFDDAK480TGB, MTFDDAK960TGB, MTFDDAK1T9TGB

Firmware D4MU404 is applicable to all configurations of 3.8TB:

MTFDDAK3T8TGA, MTFDDAK3T8TGB

Firmware D4MU804 is applicable to all configurations of 7.6TB:

MTFDDAK7T6TGA

Firmware Update Instructions Using mseccli

Firmware update requires:

- administrator or root user privileges

1. Download the latest version of mseccli from micron.com:

<https://www.micron.com/products/solid-state-storage/storage-executive-software>

2. Download the desired firmware file from micron.com

3. List the drives in the system using:

mseccli -L

4. Apply the firmware update to the desired 5400 indicated by "Device Name" using mseccli:

mseccli -F -U <firmware.bin> -n <Device_Name>

Windows example:

mseccli -F -U 5400_D4MU[048]04_combined.bin -n drive1

Linux example:

mseccli -F -U 5400_D4MU[048]04_combined.bin -n /dev/sdb